



Sovereignty Series

ISW - Internal with Winch
Wire Halyard
Ground Set Installation



ISW30C62

- SAT




TRK-9660

Int. Revolving Truck
Sealed Bearings



BAL-0612-GLD-ES

HD Gold Anodized
Aluminum Ball



COL1-A06S

FC-11 Spun Alum
1-Piece



SAT

Satin Finish



ISW - WINCH

Reinforced Raised
Door Frame

| Specifications | |
|--|----------|
| A. Mounting Height: | 30' |
| B. Set Depth: | 3'-0" |
| C. Total Length: | 33'-0" |
| D. Butt Diameter: | 6" |
| E. Wall Thickness: | .156" |
| F. Top Diameter: | 3.5" |
| Flagpole Sections: | 2 |
| Shaft Weight: | 154 lbs. |
| Hardware Weight: | 22 lbs. |
| Ground Sleeve Weight: | 36 lbs. |
| * Max Flag Size: | 6' x 10' |
| * Max Wind Speed w/Nylon Flag: | 108 mph |
| * Max Wind Speed No Flag: | 174 mph |
| * Wind Speed Specifications from ANSI/NAAMM FP 1001-07 | |

| | |
|----------------|-----------|
| Customer Name: | |
| Dealer: | Qty: 1 |
| Project: | Location: |
| Notes: | |

ISW30C62G-T0Y-O2N-C0W-FSA