

Nautical Double Mast Series - NDM

Rope Halyard

External Nautical with Yardarm and Gaff Ground Set Installation

F Top Diameter Truck and Ornament (Options Available) See Specification Box **Mounting Height Upper Mast** C Total Length Alloy 6063-T6 Tapered Aluminum Tube 3/4" Pipe brace with 1/2"-13NC Stainless Steel Hardware Yardarm Length Yardarm - Tapered Aluminum Tube Alloy 6063-T6 Aluminum Pole Gaff Length Bands with Three (3) 3/8" - 16NC Stainless Steel Eyebolts and Stainless Steel Three (3) Swivel Single Pulleys **Gaff** Tapered Hardware Aluminum Tube Ten (10) Stainless Steel Swivel Flagsnaps and Alloy 6063-T6 Ten (10) Neoprene Flagsnap Covers Five (5) Halyards, #10 (5/16" Diameter) Braided Polyester Rope E Wall Thickness (Lower Mast) H Yardarm Height Alloy 6063-T6 Tapered Aluminum Tube Cleats - Five (5) Cleats, 9" Cast Aluminum \$2₹ **D** Butt Diameter Aluminum Collar (Options Available) See Specification Box NDM-GS Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Note: Foundation design not included. Foundation Tamped Dry Sand (By Installer) Set 3/16" Steel Plate Welded to Sleeve dimensions should be determined by a qualified Engineer familiar with site 3/16" Steel Support Plate Lightning Spike - 3/4" Diameter Steel Rod soil conditions.

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

NDM30D61G-T0G-O2N-SK-C0W-FSA

NDM30D61



TRK-9709 External Truck Double Revolving



COL1-A06S FC-11 Spun Alum 1-Piece



SAT

BAL-0612-GLD-HD Gold Anodized Aluminum Ball



SAT Satin Finish

Specifications	
A. Mounting Height: 30'	
B. Set Depth: 3'-0"	
C. Total Length: 33'-0"	
D. Butt Diameter: 6"	
E. Wall Thickness: .188"	
F. Top Diameter: 3.5"	
G. Yardarm Length: 8'-0"	
H. Yardarm Height: 16'-9"	
I. Gaff Length: 5'-0"	
Sections: 1 (plus 1-Pc. Mast)	
Shaft Weight: 221 lbs.	
Hardware Weight: 48 lbs.	
Ground Sleeve Weight: 36 lbs.	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP_010819_1pg - 1 -