

F Top Diameter

Nautical Double Mast Series - NDM

Rope Halyard Ground Set Installation

Truck and Ornament (Options Available)

External Nautical with Yardarm and Gaff

See Specification Box **Mounting Height Upper Mast** C Total Length Alloy 6063-T6 Tapered Aluminum Tube 3/4" Pipe brace with 1/2"-13NC Stainless Steel Hardware Yardarm Length Yardarm - Tapered Aluminum Tube Alloy 6063-T6 Aluminum Pole Gaff Length Bands with Three (3) 3/8" - 16NC Stainless Steel Eyebolts and Stainless Steel Three (3) Swivel Single Pulleys **Gaff** Tapered Hardware Aluminum Tube Ten (10) Stainless Steel Swivel Flagsnaps and Alloy 6063-T6 Ten (10) Neoprene Flagsnap Covers Five (5) Halyards, #10 (5/16" Diameter) Braided Polyester Rope E Wall Thickness (Lower Mast) H Yardarm Height Alloy 6063-T6 Tapered Aluminum Tube Cleats - Five (5) Cleats, 9" Cast Aluminum \$2₹ **D** Butt Diameter Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer NDM-GS 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Note: Foundation design not included. Foundation Tamped Dry Sand (By Installer) 3/16" Steel Plate Welded to Sleeve dimensions should be determined by a qualified Engineer familiar with site 3/16" Steel Support Plate Lightning Spike - 3/4" Diameter Steel Rod soil conditions.

Customer Name:		
Dealer:	Qty: 1	
Project:	Location:	
Notes:		


NDM35D71G-T0G-O2P-SK-C1G-FSA

NDM35D71





TRK-9709





COL1-A07S FC-11 Spun Alum 1-Piece



BAL-0812-GLD-HD Gold Anodized Aluminum Ball



SAT Satin Finish

Specifications	
A. Mounting Height: 35'	
B. Set Depth: 3'-6"	
C. Total Length: 38'-6"	
D. Butt Diameter: 7"	
E. Wall Thickness: .188"	
F. Top Diameter: 3.5"	
G. Yardarm Length: 9'-6"	
H. Yardarm Height: 21'-9"	
I. Gaff Length: 6'-0"	
Sections: 1 (plus 1-Pc. Mast)	
Shaft Weight: 270 lbs.	
Hardware Weight: 43 lbs.	
Ground Sleeve Weight: 40 lbs.	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP_010819_1pg - 1 -