

F Top Diameter

Nautical Double Mast Series - NDM

Rope Halyard Ground Set Installation

Truck and Ornament (Options Available)

See Specification Box

External Nautical with Yardarm and Gaff

Upper Mast Mounting Height C Total Length Alloy 6063-T6 Tapered Aluminum Tube 3/4" Pipe brace with 1/2"-13NC Stainless Steel Hardware Yardarm Length Yardarm - Tapered Aluminum Tube Alloy 6063-T6 Aluminum Pole Gaff Bands with Length Three (3) 3/8" - 16NC Stainless Steel Eyebolts and Stainless Steel Three (3) Swivel Single Pulleys Gaff Tapered Hardware Aluminum Tube Ten (10) Heavy-Duty Stainless Steel Swivel Flagsnaps and Alloy 6063-T6 Ten (10) Neoprene Flagsnap Covers Five (5) Halyards, Heavy-Duty #12 (3/8" Diameter) Braided Polyester Rope E Wall Thickness (Lower Mast) H Yardarm Height Alloy 6063-T6 Tapered Aluminum Tube Cleats - Five (5) Cleats, 9" Cast Aluminum NDM-GS-1012 \$2 **D** Butt Diameter Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube Depth Note: Foundation design Tamped Dry Sand (By Installer) not included. Foundation Set 3/16" Steel Plate Welded to Sleeve dimensions should be determined by a qualified 3/16" Steel Support Plate Engineer familiar with site Lightning Spike - 3/4" Diameter Steel Rod soil conditions.

| Customer Name: | |
|----------------|-----------|
| Dealer: | Qty: 1 |
| Project: | Location: |
| Notes: | |
| | |
| | |
| | |
| | |

NDM60F23G-TAX-O0G-SK-C2P-FSA

NDM60F23



TRK-9975-58 HD Truck - Double Rev. Sealed Bearings



SAT

BAL-1258-GLD HD Gold Anodized Aluminum Ball



COL1-A12C FC-11 Cast Alum 1-Piece



SAT Satin Finish

| Specifications |
|----------------------------------|
| A. Mounting Height: 60' |
| B. Set Depth: 6'-0" |
| C. Total Length: 66'-0" |
| D. Butt Diameter: 12" |
| E. Wall Thickness: .250" |
| F. Top Diameter: 4" |
| G. Yardarm Length: 16'-0" |
| H. Yardarm Height: 31'-8" |
| I. Gaff Length: 10'-9" |
| Sections: 3 (plus 1-Pc. Mast) |
| Shaft Weight: 800 lbs. |
| Hardware Weight: 58 lbs. |
| Ground Sleeve Weight: 85 lbs. |
| |
| * Wind Speed Specifications from |
| |

ANSI/NAAMM FP 1001-07

CAFP_010819_1pg - 1 -