

Nautical Single Mast Series - NSM

Rope Halyard Ground Set Installation

External Nautical with Yardarm

F Top Diameter Truck and Ornament (Options Available) See Specification Box A Mounting Height **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube Extruded Aluminum Pole Bands with Stainless Steel Hardware Yardarm Length Yardarm - Tapered Aluminum Tube Alloy 6063-T6 C Total Length Two (2) 3/8" - 16NC Stainless Steel Eyebolts and Two (2) Swivel Single Pulleys Six (6) Stainless Steel Swivel Flagsnaps and Six (6) Neoprene Flagsnap Covers Three (3) Halyards, #10 (5/16" Diameter) H Yardarm Height Braided Polyester Rope Cleats - Three (3) Cleats, 9" Cast Aluminum **NSM-GS D** Butt Diameter Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube B Set Depth Tamped Dry Sand (By Installer) Note: Foundation design 3/16" Steel Plate Welded to Sleeve not included. Foundation dimensions should be determined by a qualified 3/16" Steel Support Plate 12"6" Lightning Spike -Engineer familiar with site soil conditions 3/4" Diameter Steel Rod

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

NSM30B51G-T0F-O2M-SK-C0L-FSA

NSM30B51



TRK-9610

In-Line Truck Single Revolving



SAT

HD Gold Anodized Aluminum Ball



COL1-A05S FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications
A. Mounting Height: 30'
B. Set Depth: 3'-0"
C. Total Length: 33'-0"
D. Butt Diameter: 5"
E. Wall Thickness: .125"
F. Top Diameter: 3"
G. Yardarm Length: 8'-0"
H. Yardarm Height: 18'-0"
Flagpole Sections: 1
Shaft Weight: 131 lbs.
Hardware Weight: 19 lbs.
Ground Sleeve Weight: 29 lbs.
* Wind Speed Specifications from
A NICU/NIA A NANA ED 4004 07

ANSI/NAAMM FP 1001-07

CAFP_010819_1pg - 1 -