

## **Nautical Single Mast Series - NSM**

Rope Halyard Ground Set Installation

## **External Nautical with Yardarm**

## F Top Diameter Truck and Ornament (Options Available) See Specification Box A Mounting Height **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube Extruded Aluminum Pole Bands with Stainless Steel Hardware Yardarm Length Yardarm - Tapered Aluminum Tube Alloy 6063-T6 C Total Length Two (2) 3/8" - 16NC Stainless Steel Eyebolts and Two (2) Swivel Single Pulleys Six (6) Stainless Steel Swivel Flagsnaps and Six (6) Neoprene Flagsnap Covers Three (3) Halyards, #10 (5/16" Diameter) H Yardarm Height Braided Polyester Rope Cleats - Three (3) Cleats, 9" Cast Aluminum **NSM-GS D** Butt Diameter Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube B Set Depth Tamped Dry Sand (By Installer) Note: Foundation design 3/16" Steel Plate Welded to Sleeve not included. Foundation dimensions should be determined by a qualified 3/16" Steel Support Plate 12"6" Lightning Spike -Engineer familiar with site soil conditions 3/4" Diameter Steel Rod

Customer Name:		
Dealer:		Qty: 1
Project:	Location:	
Notes:		

NSM30C52G-T0F-O2M-SK-C0L-FSA

## **NSM30C52**



TRK-9610

In-Line Truck Single Revolving



SAT

BAL-0512-GLD-

**HD Gold Anodized** Aluminum Ball



COL1-A05S FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications	
A. Mounting Height: 30'	
B. Set Depth: 3'-0"	
C. Total Length: 33'-0"	
D. Butt Diameter: 5"	
E. Wall Thickness: .156"	
F. Top Diameter: 3"	
G. Yardarm Length: 8'-0"	
H. Yardarm Height: 18'-0"	
Flagpole Sections: 2	
Shaft Weight: 147 lbs.	
Hardware Weight: 19 lbs.	
Ground Sleeve Weight: 29 lbs.	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP\_010819\_1pg - 1 -