

## **Nautical Single Mast Series - NSM**

External Nautical with Yardarm Rope Halyard
Ground Set Installation

## F Top Diameter Truck and Ornament (Options Available) See Specification Box A Mounting Height **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube Extruded Aluminum Pole Bands with Stainless Steel Hardware Yardarm Length Yardarm - Tapered Aluminum Tube Alloy 6063-T6 C Total Length Two (2) 3/8" - 16NC Stainless Steel Eyebolts and Two (2) Swivel Single Pulleys Six (6) Stainless Steel Swivel Flagsnaps and Six (6) Neoprene Flagsnap Covers Three (3) Halyards, #10 (5/16" Diameter) H Yardarm Height Braided Polyester Rope Cleats - Three (3) Cleats, 9" Cast Aluminum **NSM-GS D** Butt Diameter Aluminum Collar (Options Available)

See Specification Box Perimeter caulked by Installer

2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer)

Tamped Dry Sand (By Installer)

3/16" Steel Support Plate

3/4" Diameter Steel Rod

Lightning Spike -

3/16" Steel Plate Welded to Sleeve

Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube

Note: Foundation design

not included. Foundation dimensions should be determined by a qualified

Engineer familiar with site soil conditions

| Customer Name: |           |
|----------------|-----------|
| Dealer:        | Qty: 1    |
| Project:       | Location: |
| Notes:         |           |
|                |           |
|                |           |
|                |           |
|                |           |

NSM35C61G-T0F-O2N-SK-C0W-FSA

B Set Depth

12"6"

## NSM35C61



TRK-9610

In-Line Truck Single Revolving



SAT

BAL-0612-GLD-ES

HD Gold Anodized Aluminum Ball



COL1-A06S FC-11 Spun Alum 1-Piece



**SAT** Satin Finish

| Specifications                   |  |
|----------------------------------|--|
| A. Mounting Height: 35'          |  |
| B. Set Depth: 3'-6"              |  |
| C. Total Length: 38'-6"          |  |
| D. Butt Diameter: 6"             |  |
| E. Wall Thickness: .156"         |  |
| F. Top Diameter: 3.5"            |  |
| G. Yardarm Length: 9'-6"         |  |
| H. Yardarm Height: 21'-0"        |  |
| Flagpole Sections: 1             |  |
| Shaft Weight: 202 lbs.           |  |
| Hardware Weight: 15 lbs.         |  |
| Ground Sleeve Weight: 40 lbs.    |  |
|                                  |  |
|                                  |  |
| * Wind Speed Specifications from |  |
| ANSI/NAAMM FP 1001-07            |  |

CAFP\_010819\_1pg -1-