

Nautical Single Mast Series - NSM

Rope Halyard Ground Set Installation

External Nautical with Yardarm

F Top Diameter Truck and Ornament (Options Available) See Specification Box A Mounting Height **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube Extruded Aluminum Pole Bands with Stainless Steel Hardware Yardarm Length Yardarm - Tapered Aluminum Tube Alloy 6063-T6 C Total Length Two (2) 3/8" - 16NC Stainless Steel Eyebolts and Two (2) Swivel Single Pulleys Six (6) Stainless Steel Swivel Flagsnaps and Six (6) Neoprene Flagsnap Covers Three (3) Halyards, #10 (5/16" Diameter) H Yardarm Height Braided Polyester Rope Cleats - Three (3) Cleats, 9" Cast Aluminum **NSM-GS D** Butt Diameter Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube B Set Depth Tamped Dry Sand (By Installer) Note: Foundation design 3/16" Steel Plate Welded to Sleeve not included. Foundation dimensions should be determined by a qualified 3/16" Steel Support Plate 12"6" Lightning Spike -Engineer familiar with site soil conditions 3/4" Diameter Steel Rod

Customer Name:		
Dealer:	Qty: 1	
Project:	Location:	
Notes:		

NSM35D71G-T0F-O2P-SK-C1G-FSA

NSM35D71





TRK-9610


In-Line Truck Single Revolving



SAT

BAL-0812-GLD-**HD Gold Anodized**

Aluminum Ball



COL1-A07S FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications	
A. Mounting Height: 35'	
B. Set Depth: 3'-6"	
C. Total Length: 38'-6"	
D. Butt Diameter: 7"	
E. Wall Thickness: .188"	
F. Top Diameter: 3.5"	
G. Yardarm Length: 9'-6"	
H. Yardarm Height: 21'-0"	
Flagpole Sections: 1	
Shaft Weight: 246 lbs.	
Hardware Weight: 15 lbs.	
Ground Sleeve Weight: 40 lbs.	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP_010819_1pg - 1 -