

Nautical Single Mast Series - NSM

Rope Halyard Ground Set Installation

External Nautical with Yardarm

Truck and Ornament (Options Available) F Top Diameter See Specification Box A Mounting Height **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube Extruded Aluminum Pole Bands **G** Yardarm with Stainless Steel Hardware Length **Yardarm** - Tapered Aluminum Tube Alloy 6063-T6 C Total Length Two (2) 3/8" - 16NC Stainless Steel Eyebolts and Two (2) Swivel Single Pulleys Six (6) Heavy-Duty Stainless Steel Swivel Flagsnaps and Six (6) Neoprene Flagsnap Covers Three (3) Halyards, Heavy-Duty #12 (3/8" Diameter) H Yardarm Height Braided Polyester Rope Cleats - Three (3) Cleats, 9" Cast Aluminum NSM-GS-1012 **D** Butt Diameter Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube **B** t Depth Tamped Dry Sand (By Installer) Note: Foundation design 3/16" Steel Plate Welded to Sleeve not included. Foundation Set dimensions should be 3/16" Steel Support Plate determined by a qualified Lightning Spike -Engineer familiar with site soil conditions. 3/4" Diameter Steel Rod

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

NSM60D13G-TAY-O0F-SK-C2C-FSA

NSM60D13



TRK-9420-58 HD Truck - Single Rev. Sealed Bearings



SAT

HD Gold Anodized Aluminum Ball



COL1-A10S FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications
A. Mounting Height: 60'
B. Set Depth: 6'-0"
C. Total Length: 66'-0"
D. Butt Diameter: 10"
E. Wall Thickness: .188"
F. Top Diameter: 4"
G. Yardarm Length: 16'-0"
H. Yardarm Height: 36'-0"
Flagpole Sections: 3
Shaft Weight: 593 lbs.
Hardware Weight: 23 lbs.
Ground Sleeve Weight: 85 lbs.
* Wind Speed Specifications from

ANSI/NAAMM FP 1001-07

CAFP 010819 1pg - 1 -