

F Top Diameter

Nautical Single Mast Series - NSM

Truck and Ornament (Options Available)

External Nautical with Yardarm Rope Halyard Ground Set Installation

See Specification Box A Mounting Height **E** Wall Thickness Alloy 6063-T6 Tapered Aluminum Tube Extruded Aluminum Pole Bands **G** Yardarm with Stainless Steel Hardware Length **Yardarm** - Tapered Aluminum Tube Alloy 6063-T6 C Total Length Two (2) 3/8" - 16NC Stainless Steel Eyebolts and Two (2) Swivel Single Pulleys Six (6) Heavy-Duty Stainless Steel Swivel Flagsnaps and Six (6) Neoprene Flagsnap Covers Three (3) Halyards, Heavy-Duty #12 (3/8" Diameter) H Yardarm Height Braided Polyester Rope Cleats - Three (3) Cleats, 9" Cast Aluminum NSM-GS-1012 **D** Butt Diameter Aluminum Collar (Options Available) See Specification Box Perimeter caulked by Installer 2" Cap - Cement or Waterproof Compound and Hardwood Wedges (By Installer) Ground Sleeve Assembly - 16 Gauge Galvanized Steel Tube **B** t Depth Tamped Dry Sand (By Installer) Note: Foundation design 3/16" Steel Plate Welded to Sleeve not included. Foundation Set dimensions should be 3/16" Steel Support Plate determined by a qualified Lightning Spike -Engineer familiar with site soil conditions. 3/4" Diameter Steel Rod

Customer Name:	
Dealer:	Qty: 1
Project:	Location:
Notes:	

NSM80H24G-TAY-O0G-C2N-FSA

NSM80H24





TRK-9420-58 HD Truck - Single Rev. Sealed Bearings



BAL-1258-GLD HD Gold Anodized Aluminum Ball



COL1-A12S FC-11 Spun Alum 1-Piece



SAT Satin Finish

Specifications	
A. Mounting Height: 80'	
B. Set Depth: 8'-0"	
C. Total Length: 88'-0"	
D. Butt Diameter: 12"	
E. Wall Thickness: .375"	
F. Top Diameter: 4"	
G. Yardarm Length: 18'-9"	
H. Yardarm Height: 48'-0"	
Flagpole Sections: 4	
Shaft Weight: 1294 lbs.	
Hardware Weight: 35 lbs.	
Ground Sleeve Weight: 106 lbs.	
* Wind Speed Specifications from	
ANSI/NAAMM FP 1001-07	

CAFP_010819_1pg - 1 -